

Poêle à bois "GIRA DA"



Declaration of Performance

acc. Annex III of Regulation (EU) No. 305/2011

DOP – No. 40 16 4343 / 27.07.2016

1. Unique identification code of the product-type:

SKI 356

Room heater in buildings without heating and water domestic hot water

EN 13240:2001/A2:2004/AC:2007

2. Intended use or uses of the constructions product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Room heater in buildings without heating and water domestic hot water.

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11, paragraph 5:

SKANDERBORG Produktions- und Vertriebs GmbH, Büssingstr. 60-62, 32257 Bünde,

www.skanderborg.de, Tel. +49 5223 - 4911067, Fax: +49 5223 – 4911068,

Email: info@skanderborg.de

4. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12, paragraph 2 :

eliminates

5. System or systems of assessment and verification of constancy of performance of the construction as set out in Annex V:

System 3

6. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

The notified laboratory of Rhein-Ruhr Feuerstätten Prüfstelle GmbH, with issued no.1625, acc. System 3 performed the initial assessment and documented in the test report RRF – 40 16 4343.

7. Declared performance:

Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	fulfilled
Reaction to fire	A1
Distance to combustible materials	Minimum distance in mm Rear: 240 Sides: 420 Front: 1200
Risk of burning fuel falling out	fulfilled
Emission of combustion products	CO=[0,09%]
Surface temperature	fulfilled
Electrical safety	not fulfilled
Cleanability	fulfilled
Release of dangerous substances	npd
Maximum operation pressure (applicable only by fireplaces equipped with water components)	„__“ bar
Flue gas temperature at nominal heat output	T [256°C]
Mechanical strength (to install flue outlet)	NPD
Heat performance / energy efficiency	fulfilled
Nominal heat output	6,2 kW
Space heating power	6,8 kW
Water pipe	-
Efficiency	82%

8. The performance of the product identified acc. point 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Bünde, 02.08.2016

Andreas Apel
General Manager